



# UltiMount **S2**

PART NUMBER: **UL-222**

---

## Pre-Installation Tips

Before installing the UltiMount **S2** determine the position where it will work best for the primary user. **Attach a holder or cradle** along with the electronic device to the UltiMount **S2** prior to exploring the ideal position for mounting. Some electronics may include a holder for a vehicle application, and if so, it will usually attach directly to the UltiMount **S2**

**Important:** The flex pad adhesive is a one-time stick application. Therefore, it is best to determine the mounting position for the UltiMount **S2** prior to installing. Once the flex pad is adhered to the mounting surface, it cannot be repositioned. Be sure to complete all surface preparation steps before installing UltiMount **S2**.

## Installation Instructions

Please read all instructions thoroughly before installing this product.

**Contents:** UltiMount **S2**, Surface Preparation Packet, Alcohol Prep Pad

**Helpful items to have:** Clean dry cloth

**Important:** Clean the surface where the UltiMount **S2** will be installed with the Surface Prep Packet to remove the silicone emulsions such as Armor All®. Do not apply adhesive to leather surfaces. Do not install the UltiMount **S2** where it could block your vision, airbags, gear shifter, climate controls, steering wheel, radio controls, or other amenities that may interfere with safe operations of the vehicle.

### Step One:

Position and select the best mounting location on the dash or console of the vehicle where the UltiMount **S2** is to be installed.

### Step Two:

Prepare the mounting surface by cleaning the mounting location with the Surface Preparation Packet provided. Wipe an area slightly larger than the flex pad in only one direction and do not use a circular motion. Dry the area with a clean, dry cloth. Wipe dry in the same direction as above.

Clean the same area with the Alcohol Prep Pad provided. Wipe in the same direction as above, dry with a clean cloth and allow to air dry completely.

*Note:* The alcohol may leave a film on the surface. Wipe clean with a dry cloth.

### Step Three:

It is best to remove the flex pad from the UltiMount **S2** before adhering. Remove the flex pad from the gray ball and stem with a phillips screwdriver. Access this screw through the hole in the gray ball. Remove the liner from adhesive pad and adhere it to the mounting position. Apply firm pressure to the center and edges of the flex pad for a minimum of 1 minute. Let adhesive cure for 72 hours before reattaching the UltiMount **S2**.

Ideal installation temperature is between 60° and 80°F.



## UltiMount S2

PART NUMBER: **UL-222**

### Flex Pad Removal Instructions:

Please read all instructions thoroughly before attempting

**Step 1** If the mounting surface appears to be highly decorative, no removal tools are recommended. Remove by hand and proceed with caution. If the mounting surface is vinyl, a blunt instrument may help to remove the flex pad. A kitchen spoon may work well. Avoid using tools with sharp edges that may damage the mounting surface.

**Step 2** Warm the Flex Pad with a hair dryer for 2 to 3 minutes. Once the flex pad has been heated, the adhesive will soften. Caution: Too much heat may damage the vehicle or mounting surface. Do not use a commercial heat gun or paint stripping gun as these will create excessive heat.

**Step 3** Lift one edge of the flex pad gently with your fingers or the rounded edge of the spoon. Once enough of the edge is peeled up to grip with your fingers, pull the flex pad gently at a 90 degree angle from the mounted surface until removed.

**Step 4** In most cases there will be no adhesive left on the mounting surface. If you find that adhesive remains, it can be easily removed by rubbing your thumb or finger across the surface repeatedly.

### Optional Accessories Sold Separately

T-Amps Adapter Plate	<i>mi</i> Mount iPod Cradle
<i>mi</i> Grip Universal Holder	<i>mini</i> Grip Universal Holder
Express Mount	Extension Bracket



**Bolt-on Plate Available at [www.pro-fit-intl.com](http://www.pro-fit-intl.com)**

Pro.Fit International, Inc.® may not be held liable for any damage to a vehicle before, during or after the installation or removal of this Pro.Fit Universal Mount®. Pro.Fit may not be held liable for any personal injury resulting from accident or improper installation. Pro.Fit International, Inc.® 1335 Eagandale Court, Eagan, MN 55121, Ph: 651.688.3588 or 800.388.0073 Fx: 651.688.9876

© Pro.Fit International, Eagan, MN 2007

**VIEW INSTRUCTIONS & UPDATES  
ONLINE @  
[WWW.PRO-FIT-INTL.COM](http://WWW.PRO-FIT-INTL.COM)**